

**ZINOX Z-NANO PRO - PROFESSIONAL
NANO PROTECTION
FOR ASPHALT SHINGLES**

DESCRIPTION	TECHNICAL DATA
Professional clear nano coating designed for asphalt shingle surfaces. Z-Nano Pro helps protect against moisture and UV exposure, slow granule loss, and extend the service life of the roof covering while preserving the shingle's natural appearance.	SKU: Z-810-00 Color: Clear liquid Odor: Mild Gloss 60°: 60 - 70° Viscosity: 26 ± 2 Zahn #2 Coverage: Approx. 1,500 ft² / 5 gallons in one coat. VOC: ≤ 135 g/L WFT: 1.0 - 1.5 mils, 25.0 - 37.5 microns per coat DFT: 2.8 - 4.0 mils Density: 1.1 ± 0.05 pH: 8.2 - 8.7 Weight / gallon: 8.45 ± 0.25 lb Solids / weight: 30 ± 1 % Solids / volume: 28 ± 1 % Composition: Binder: 100% acrylic emulsion Thinner: Water, Glycol Ether
USE	
PROFESSIONAL USE - APPLY WITH A GRACO-TYPE AIRLESS PUMP. Recommended for asphalt shingle surfaces. One uniform coat is recommended. Estimated product service life: 8 years when recommended preparation and application procedures are followed.	
SURFACE PREPARATION	
Surfaces must be clean, dry and free of contaminants. Pre-clean with Z-Cleaner, SKU Z-200-00 , then rinse thoroughly with clean water. Allow the surface to dry completely before applying Z-810-00.	
APPLICATION	Temperature: 15 to 30 °C (59 to 86 °F) Humidity: Ideal 50%. Maximum 85%. Dry time (at 25 °C and 50% humidity): Touch dry: 1 hour Cure: 16 hours Drying time may vary with humidity, temperature, texture and surface porosity.
THINNING	
None. Ready to use.	
TOOL CLEANUP	Sprayer: Professional Graco-type electric airless pump Recommended model: Graco 390 or equivalent Pressure: 1,500 - 2,500 psi Tip: 0.011 - 0.015 in. orifice
WASTE DISPOSAL	STORAGE Store in a ventilated, cool and dry area between 10 °C and 25 °C. Keep containers closed when not in use. Protect from freezing. Shelf life: 1 year in unopened containers stored in a cool, dry place.
	WARRANTY For any express or implied warranty, whether contractual or arising by law, the manufacturer's liability is limited to replacement of merchandise found defective at the time of inspection. The manufacturer is not responsible for warranties made by agents, representatives or employees concerning the merchandise or product in this container.
	SAFETY INFORMATION Flash point: None Lead content: None Mercury content: None Consult the product Safety Data Sheet (SDS) for health and safety information and review label directions before use.